



EDISON OPTO CORPORATION

Edixeon Emitter

1W High Power LED



DATE : 2005/04/30

VERSION : 2.3

Device No. : 3-RD-01-E0001



EDISON OPTO CORPORATION
Office: 4F, No. 800, Chung-Cheng Rd,
Chung-Ho, Taipei 235, Taiwan, R.O.C.

Tel: 886-2-8227-6996
Fax: 886-2-8227-6997
<http://www.edison-opto.com.tw>

Features

- Long operating life (up to 100,000 hours)
- More Energy Efficient than incandescent and most halogen lamps
- Low forward voltage operated
- Instant light (Less than 100 ns)
- No UV
- High ESD protection.(More than 8kV).


Typical Applications

- Reading lights
- Portable flashlight
- Uplighters and Downlighters
- Bollards / Security / Garden lighting
- Indoor and Outdoor Commercial lighting
- LCD Backlights / Light guides
- General lighting


Edixeon Emitter group

White Housing	<u>Emitter</u>	White	Warm White	Red	Green
	Lambertian	EDEW-1LA1	EDEX-1LA1	EDER-1LA3	EDET-1LA2
	Batwing	EDEW-1BA1	EDEX-1BA1	EDER-1BA3	EDET-1BA2
	Side Emitting	EDEW-1SA1	EDEX-1SA1	EDER-1SA3	EDET-1SA2
	Focusing	EDEW-1FA1	EDEX-1FA1	EDER-1FA3	EDET-1FA2
	<u>Emitter</u>	Blue	Red Orange	Amber	
	Lambertian	EDEB-1LA1	EDEO-1LA3	EDEA-1LA3	
	Batwing	EDEB-1BA1	EDEO-1BA3	EDEA-1BA3	
	Side Emitting	EDEB-1SA1	EDEO-1SA3	EDEA-1SA3	
	Focusing	EDEB-1FA1	EDEO-1FA3	EDEA-1FA3	

Lambertian Package Outlines







Side Emitting Package Outlines







Unit:mm

Batwing Package Outlines



Focusing Package Outlines




Unit:mm

Absolute Maximum Ratings

Parameter	Symbol	Rating	Units
DC Forward Current	I_F	350	mA
Peak pulse current; ($t_p \leq 100\mu s$, Duty cycle=0.005) ^{*1}	I_{pulse}	1000	mA
Reverse Voltage	V_R	5	V
LED junction Temperature (at 350 mA)	T_j	125	°C
Operating Temperature	T_{opr}	-30 ~ +110	°C
Storage Temperature	T_{stg}	-40 ~ +120	°C
Manual Soldering Time at 260°C (Max.)	T_{sol}	5	seconds

1. Duty cycle:



Luminous Flux

Characteristics at $I_F=350mA(T_a=25^\circ C)$:

Lens Item	Part Name	Color	Flux			Units
			Min.	Typ.	Max.	
Lambertian	EDEW-1xx1	White	23.3	40.0	--	lm
	EDEX-1xx1	Warm White	17.9	22.0	--	lm
	EDER-1xx3	Red	17.9	26.0	--	lm
	EDEO-1xx3	Red Orange	23.3	35.0	--	lm
	EDEA-1xx3	Amber	23.3	30.0	--	lm
	EDET-1xx2	True Green	23.3	35.0	--	lm
	EDEB-1xx1	Blue	6.3	10.0	--	lm

Lens Item	Part Name	Color	Flux			Units
			Min.	Typ.	Max.	
Batwing Focusing Side Emitting	EDEW-1xx1	White	23.3	36.0	--	lm
	EDEX-1xx1	Warm White	17.9	20.0	--	lm
	EDER-1xx3	Red	17.9	23.0	--	lm
	EDEO-1xx3	Red Orange	23.3	32.0	--	lm
	EDEA-1xx3	Amber	23.3	27.0	--	lm
	EDET-1xx2	True Green	23.3	32.0	--	lm
	EDEB-1xx1	Blue	6.3	9.0	--	lm

Forward Voltage

Characteristics at $I_F=350mA(T_a=25^\circ C)$:

Lens Item	Part Name	Color	V_F			Units
			Min.	Typ.	Max.	
Lambertian Side Emitting Batwing Focusing	EDEW-1xx1	White	2.8	--	4.0	V
	EDEX-1xx1	Warm White	2.8	--	4.0	V
	EDER-1xx3	Red	2.0	--	2.75	V
	EDEO-1xx3	Red Orange	2.0	--	2.75	V
	EDEA-1xx3	Amber	2.0	--	2.75	V
	EDET-1xx2	True Green	2.8	--	4.0	V
	EDEB-1xx1	Blue	2.8	--	4.0	V

Wavelength or Color Temperature

Characteristics at $I_F=350mA(T_a=25^\circ C)$:

Lens Item	Part Name	Color	λ_d/CCT			Units
			Min.	Typ.	Max.	
Lambertian Side Emitting Batwing Focusing	EDEW-1xx1	White	5000	--	8000	K
	EDEX-1xx1	Warm White	2800	--	3800	K
	EDER-1xx3	Red	620	--	630	nm
	EDEO-1xx3	Red Orange	610	--	620	nm
	EDEA-1xx3	Amber	585	--	595	nm
	EDET-1xx2	True Green	515	--	535	nm
	EDEB-1xx1	Blue	460	--	475	nm

Thermal Resistance Junction to Board
Characteristics at $I_F=350mA(T_a=25^\circ C)$:

Lens Item	Part Name	Color	R θ_{J-B}			Units
			Min.	Typ.	Max.	
Lambertian Side Emitting Batwing Focusing	EDEW-1xx1	White	--	15	--	$^\circ C/W$
	EDEX-1xx1	Warm White	--	15	--	$^\circ C/W$
	EDER-1xx3	Red	--	15	--	$^\circ C/W$
	EDEO-1xx3	Red Orange	--	15	--	$^\circ C/W$
	EDEA-1xx3	Amber	--	15	--	$^\circ C/W$
	EDET-1xx2	True Green	--	15	--	$^\circ C/W$
	EDEB-1xx1	Blue	--	15	--	$^\circ C/W$

Temperature Coefficient Of Forward Voltage
Characteristics at $I_F=350mA(T_a=25^\circ C)$:

Lens Item	Part Name	Color	$\Delta V_F/\Delta T$			Units
			Min.	Typ.	Max.	
Lambertian Side Emitting Batwing Focusing	EDEW-1xx1	White	--	-2	--	mV/ $^\circ C$
	EDEX-1xx1	Warm White	--	-2	--	mV/ $^\circ C$
	EDER-1xx3	Red	--	-2	--	mV/ $^\circ C$
	EDEO-1xx3	Red Orange	--	-2	--	mV/ $^\circ C$
	EDEA-1xx3	Amber	--	-2	--	mV/ $^\circ C$
	EDET-1xx2	True Green	--	-2	--	mV/ $^\circ C$
	EDEB-1xx1	Blue	--	-2	--	mV/ $^\circ C$

Reverse Current
Characteristics at $V_R=5V(T_a=25^\circ C)$:

Lens Item	Part Name	Color	$I_R(V_R=5V)$			Units
			Min.	Typ.	Max.	
Lambertian Side Emitting Batwing Focusing	EDEW-1xx1	White	--	--	50	μA
	EDEX-1xx1	Warm White	--	--	50	μA
	EDER-1xx3	Red	--	--	50	μA
	EDEO-1xx3	Red Orange	--	--	50	μA
	EDEA-1xx3	Amber	--	--	50	μA
	EDET-1xx2	True Green	--	--	50	μA
	EDEB-1xx1	Blue	--	--	50	μA

Emission Angle

Characteristics at $I_F=350mA(T_a=25^\circ C)$:

Lens Item	Part Name	Color	$2\Theta^{1/2}$			Units
			Min.	Typ.	Max.	
Lambertian	EDEW-1Lx1	White	--	140	--	Degrees
	EDEX-1Lx1	Warm White	--	140	--	Degrees
	EDER-1Lx3	Red	--	120	--	Degrees
	EDEO-1Lx3	Red Orange	--	120	--	Degrees
	EDEA-1Lx3	Amber	--	120	--	Degrees
	EDET-1Lx2	True Green	--	140	--	Degrees
	EDEB-1Lx1	Blue	--	140	--	Degrees

Lens Item	Part Name	Color	Θ_{PEAK}			Units
			Min.	Typ.	Max.	
Side Emitting	EDEW-1Sx1	White	--	80	--	Degrees
	EDEX-1Sx1	Warm White	--	80	--	Degrees
	EDER-1Sx3	Red	--	75	--	Degrees
	EDEO-1Sx3	Red Orange	--	75	--	Degrees
	EDEA-1Sx3	Amber	--	75	--	Degrees
	EDET-1Sx2	True Green	--	80	--	Degrees
	EDEB-1Sx1	Blue	--	80	--	Degrees

Emission Angle

Characteristics at $I_F=350mA(T_a=25^\circ C)$:

Lens Item	Part Name	Color	$2\Theta^{1/2}$			Units
			Min.	Typ.	Max.	
Focusing	EDEW-1Fx1	White	--	85	--	Degrees
	EDEX-1Fx1	Warm White	--	85	--	Degrees
	EDER-1Fx3	Red	--	55	--	Degrees
	EDEO-1Fx3	Red Orange	--	55	--	Degrees
	EDEA-1Fx3	Amber	--	55	--	Degrees
	EDET-1Fx2	True Green	--	60	--	Degrees
	EDEB-1Fx1	Blue	--	60	--	Degrees




Lens Item	Part Name	Color	$2\Theta^{1/2}$	Θ_{PEAK}	Units
			Typ.	Typ.	
Batwing	EDEW-1Bx1	White	110	40	Degrees
	EDEX-1Bx1	Warm White	110	40	Degrees
	EDER-1Bx3	Red	110	35	Degrees
	EDEO-1Bx3	Red Orange	110	35	Degrees
	EDEA-1Bx3	Amber	110	35	Degrees
	EDET-1Bx2	True Green	110	40	Degrees
	EDEB-1Bx1	Blue	110	40	Degrees

Note


1. Flux is measured with an accuracy of $\pm 15\%$.
2. CCT selection acc. to CCT groups and an accuracy of $\pm 400K$
3. Forward Voltage is measured with an accuracy of $\pm 0.2V$.
4. Wavelength is measured with an accuracy of $\pm 3nm$
5. Angle is measured with an accuracy of ± 15 degree

Electrical & Optical Curves


Wavelength Spectrum




Typical Radiation Pattern for Lambertian




Typical Radiation Pattern for Side Emitting




Typical Radiation Pattern for Batwing




Typical Radiation Pattern for Focusing





Operating Current & Ambient Temperature



Current & Luminous Flux



Operating Current & Forward Voltage



Light Output & Junction Temperature

